



ULTRASUN i8 POWERTOWER

TECHNICAL DETAILS

Total Lamps	48 x Sunfit XXL3 200W E-Tronic 200cm
Power Consumption	± 8.400 Watt
Power Supply	50 Amps single or 16 Amps per phase TPN&E
Breaker	Type C Breaker
Weight	290 Kg
Colour Options	Dream White Metallic, Sunny Silver Metallic, Xtreme Orange Metallic <i>(Subject to availability)</i>

FEATURES



Solar Control



Top Cooler



Air Extraction
Hose



Mood Light

Changing Cubicle also available

DIMENSIONS (OPEN)



Length = Door open dimension
Width = Door closed dimension
Height = Floor to ceiling

VENTILATION

The ventilation output is 1700 cubic metres of air per hour.

1 x 10cm diameter flexible duct is fitted to the rear of the machine. The duct can be fitted into a ventilation system or vented out to atmosphere providing this is not further than 3 metres from the sunbed.

**ANY QUERIES? PLEASE CALL
HELIONOVA ON 01603 789 010**

ELECTRICAL REQUIREMENTS

Three Phase Supply

Socket Requirement	16 amps per phase TPN&E. Female commando socket
Trip Size	16 amps per phase C Type

Single Phase Supply

Socket Requirement	63 amp. Female commando socket
Trip Size	50 amp. C Type

Each machine will have a male commando plug fitted with a minimum of 2.5m flex. If position of female socket requires a longer flex, please inform us prior to installation.



Changes in prices, technical specifications and design are reserved | 01-01-23 | V1