



GARDASUN SUNRISE 7000

TECHNICAL DETAILS

Total Lamps	42 x Sunfit XL3 180W E-Tronic 180 cm
Power Consumption	± 7,000 W
Power Supply	40 Amps single or 16 Amps per phase TPN&E
Breaker	Type C Breaker
Weight	220 Kg
Colour Options	Sunny Silver Metallic <i>(Subject to availability)</i>

FEATURES



Lumax
Control

Changing Cubicle also available.

DIMENSIONS (OPEN)



Length = Door open dimension
Width = Door closed dimension
Height = Floor to ceiling

VENTILATION

The ventilation output is 500 cubic metres of air per hour.

Provision must be made for general room ventilation.

**ANY QUERIES? PLEASE CALL
HELIONOVA ON 01603 789 010**

ELECTRICAL REQUIREMENTS

Three Phase Supply

Socket Requirement	16 amps per phase TPN&E. Female commando socket
Trip Size	16 amps per phase C Type

Single Phase Supply

Socket Requirement	63 amp. Female commando socket
Trip Size	40 amp. C Type

Each machine will have a male commando plug fitted with a minimum of 2.5m flex. If position of female socket requires a longer flex, please inform us prior to installation.



Changes in prices, technical specifications and design are reserved | 01-01-23 | V1