



# GARDASUN SUNSHINE 7000

## TECHNICAL DETAILS

Total Lamps	42 x Sunfit XL3 200W E-Tronic   190 cm
Power Consumption	± 7,300 W
Power Supply	50 Amps single or 16 Amps per phase TPN&E
Breaker	Type C Breaker
Weight	235 Kg
Colour Options	Ice Blue Metallic <i>(Subject to availability)</i>

## FEATURES



Solar  
Control



Top  
Cooler

Changing Cubicle also available.

## DIMENSIONS (OPEN)



Length = Door open dimension  
Width = Door closed dimension  
Height = Floor to ceiling

## VENTILATION

The ventilation output is 500 cubic metres of air per hour.

Provision must be made for general room ventilation.

**ANY QUERIES? PLEASE CALL  
HELIONOVA ON 01603 789 010**

## ELECTRICAL REQUIREMENTS

### Three Phase Supply

Socket Requirement	16 amps per phase TPN&E. Female commando socket
Trip Size	16 amps per phase C Type

### Single Phase Supply

Socket Requirement	63 amp. Female commando socket
Trip Size	50 amp. C Type

Each machine will have a male commando plug fitted with a minimum of 2.5m flex. If position of female socket requires a longer flex, please inform us prior to installation.



*Changes in prices, technical specifications and design are reserved | 01-01-23 | V1*