



ULTRASUN Q10 MAGNUM

TECHNICAL DETAILS

Top Lamps	22 x Sunfit VRX3 160W E-Tronic 176 cm
Base Lamps	16 x Sunfit XL3 120W E-Tronic 190 cm
Facial Lamps	3 x Sunfit Sunfit WL 500W
Shouldertanner	5 x Sunfit S 25W Spaghetti Tubes
Power Consumption	± 7,200 W
Power Supply	50 Amps single or 16 Amps per phase TPN&E
Breaker	Type C Breaker
Colour Options	Dream White Metallic, Silver Blue Metallic, Xtreme Orange Metallic, Royal Blue Metallic <i>(Subject to availability)</i>

FEATURES



IQ Touch Control



Body Cooler



Facial Lamps



Shoulder Tanner

DIMENSIONS (OPEN)



Dimensions LxWxH of the sunbed with the canopy open.

VENTILATION

The ventilation output is 1700 cubic metres of air per hour.

2 x 20cm diameter flexible ducts are fitted to the rear of the machine. The ducts can be fitted into a ventilation system or vented out to atmosphere providing this is not further than 3 metres from the sunbed.

ANY QUERIES? PLEASE CALL
HELIONOVA ON 01603 789 010

ELECTRICAL REQUIREMENTS

Three Phase Supply

Socket Requirement	16 amps per phase TPN&E. Female commando socket
Trip Size	16 amps per phase C Type

Single Phase Supply

Socket Requirement	63 amp. Female commando socket
Trip Size	50 amp. C Type

Each machine will have a male commando plug fitted with a minimum of 2.5m flex. If position of female socket requires a longer flex, please inform us prior to installation.



Changes in prices, technical specifications and design are reserved | 01-01-23 | V1